



Technical Data

RRL 200

Engine	Deutz TCD 3.6 L4 Stage V
Cylinders	R-4
Capacity	3,6 l
Rated power	143 hp / 105 kW
Rated speed	2,300 rpm – limited to max. 1,600 rpm
Maximum torque at 1,600 rpm	550 Nm
Fuel-tank capacity	Approx. 320 l
AdBlue-tank capacity	Approx. 19 l

Chassis

Axles	2 braked stub axles
Track width	2,42 m
Tyres	540/65 R30 – Tyre pressure 2.5 bar
Brakes	Compressed-air brake system
Towing connection	40 mm eyelet
Supporting legs	Front and rear, hydraulically foldable

Bunker

Bunkercapacity	9 m <sup>3</sup> (hydraulically foldable bunker walls)
Scraper floor	Screw-on, wear-resistant guide rails 2 round steel chains with automatic speed regulation by metering flap
Control	Teleradio radio remote control for operating all functions
Cleaning	Can be equipped in different ways for sugar beet, potatoes or chicory
Cross belt	Adjustable speed, sections: 50 mm
Transfer belt	Adjustable speed, plastic carriers, sections: 50 mm
Safety features	Finger roller-cleaning system and stone-separating roller automatically reverses

Dimensions & weights

Transport dimensions	10.62 m / 3.00 m / 3.60 m (Length / Width / Height)
Transfer height / width	5.50 m / 9.50 m, up to 125° swivel angle
Transfer capacity	Approx. 200 t/h
Max. permissible speed	40 km/h
Tare weight	Approx. 10,5 t (1,7 t permissible supported load)

Subject to modifications for technical progress; approved by TÜV and the trade association; in accordance with the CE regulations. Machine equipment depending on country-specific formalities..